



# ESEEK-TWINS

## Advantages



### Worry-free Installation

Omni-directional Adjustment for Easy Installation

- Universal joint drive shaft, adjustable up to  $\pm 15^\circ$  in all directions (front, back, left, right)
- Diameter shrinkage process for torque tube connection
- Quick-install purlin system



### Ultimate Safety

Protection Against Strong Winds

- All posts self-locking
- Axisymmetric damping
- Large-angle wind-facing protection reduces wind load torque coefficient, minimizing flutter and vortex vibration risks
- Certified by CPP wind tunnel testing



### Stable and Reliable

Stable Craftsmanship and Reliable Structure

- Diamond-shaped locking torque tube
- Openable bearing housing system
- Stable production process
- Enhanced protection against fatigue damage in carriage bolt nodes



### Superior Efficiency

Smart Commissioning for Effortless and Worry-Free Operation

- Mobile app commissioning for tracking system
- Intelligent AI tracking algorithm
- Multiple power supply and communication guarantees

## Introduction



The ESEEK-Twins tracker is a 1P dual-row linked tracking system, designed with the concept of **optimizing both safety and cost**.

## Product Parameters

● <b>Tracking Type</b>	Dual row single-axis tracker (SAT)	● <b>Module Compatibility</b>	Compatible with all types of module
● <b>Tracking Range of Motion</b>	±60°	● <b>Operation Temperature</b>	-40 to 60°C (Optional ultra-low temperature battery is required if the temperature is below -25°C)
● <b>Drive Device/Number</b>	Rotary Slew driver (single point)	● <b>Slope Adaptation</b>	≤15%(S-N and E-W)
● <b>Protection Strategy</b>	60° large-angle + all posts self-locking	● <b>Control Algorithm/Controller</b>	Astronomical algorithm & position sensor closed-loop control
● <b>Number of Module per Tracking System</b>	≤60 pcs	● <b>Tracking Accuracy</b>	≤ 1°
● <b>Power Supply Voltage</b>	≤30V (default, optional ≤1500V)	● <b>Backtracking</b>	Available
● <b>Foundation Options</b>	Ramming pile/concrete pile/PHC pile	● <b>Communication Options</b>	Wireless communication (Lora, Zigbee)
● <b>Structural Materials</b>	Hot dipped galvanized/ZAM high-strength steel	● <b>Other Optional Modes</b>	Snow, flood, and hailstone modes
● <b>Daily Power Consumption</b>	0~0.03 kWh/day/tracker	● <b>Power Supply</b>	String/small module/AC power supply with lithium battery backup
● <b>Design Wind Speed</b>	Up to 70 m/s	● <b>Warranty Period</b>	Structural components: 10 years Drive and electrical control components: 5 years



**700MW** Fushan Gonghe Source-Network-Load-Storage Yellow River Photovoltaic Project



**13.6MW** Single-Axis Tracking Bracket Photovoltaic Station Project in Tocantins, Brazil

